

STACKDOOR CORNER DATASHEET



STACK TECHNOLOGY

- Secure corner detail with no guide rail
- Small stacking zone at high level
- More than 80% free airflow
- Large maximum width
- Self-locking without auxiliary locks, to resist lifting
- Suitable for open plan applications



TYPICAL **APPLICATIONS**

- Interior retail outlets & kiosks
- Restaurants & Bars
- Residential entrances

OPTIONS

• Stainless Steel or Polyester powder coated to any standard Ral/BS colour



STACKDOOR CORNER DATASHEET

STACKDOOR CURTAIN

 Stainless steel pins secured into horizontal stainless steel bars

BOTTOM RAIL AND FRAMES

- Stainless steel bottom rail section
- Heavy duty extruded aluminium guide rails anchored direct to the structure
- No intermediate guides necessary

OPERATION

- Motorised to allow controlled ascent and descent
- Tube Motor for low duty cycle
- External Drive Motor for high duty cycle

CONTROLS

- Range of compatible controls including rotary switch, key switch, remote (control) and emergency manual crank
- Safety as assessment directs

APPROVED DIMENSIONS

- Minimum width: 1000mm | Minimum height: 500mm
- Maximum width: 20000mm | Maximum height: 7000mm



▲ 1 Darwin Close, Reading RG2 0TB United Kingdom
↓ +44 (0)845 050 8705 Stackdoor@charter-global.com
www.stackdoor.eu





DISTRIBUTOR