



STACKDOOR®

STACKDOOR CURVED DATASHEET



STACK TECHNOLOGY

- Small stacking zone at high level
- More than 80% area
- Large maximum width
- Self-locking without auxiliary locks, to resist lifting
- Curve in plan to follow building profile
- Suitable for applications with limited head-room



TYPICAL APPLICATIONS

- Automatic revolving doors
- Restaurants & Bars
- Shopping Centres & kiosks
- Retail outlets with curved entrances
- Airports & Stations

OPTIONS

- Stainless Steel or Polyester powder coated to any standard Ral/BS colour



STACKDOOR®

STACKDOOR CURVED DATASHEET

STACKDOOR CURTAIN

- Stainless steel pins secured into horizontal stainless steel bars

BOTTOM RAIL AND FRAMES

- Stainless steel bottom rail section
- Heavy duty extruded aluminium guide rails anchored direct to the structure
- No intermediate guides necessary

OPERATION

- Motorised to allow controlled ascent and descent
- Tube Motor - Low duty cycle, or where limited to single phase supply
- External Drive Motor

CONTROLS

- Range of compatible controls including rotary switch, key switch, remote (control) and emergency manual crank
- Safety as assessment directs

APPROVED DIMENSIONS

- Minimum width: 1000mm | Minimum height: 500mm
- Maximum width: 20000mm | Maximum height: 7000mm

**CHARTER
GLOBAL**

PROTECTING PEOPLE | SECURING PROPERTY

🏠 1 Darwin Close, Reading RG2 0TB United Kingdom

☎ +44 (0)845 050 8705 ✉ stackdoor@charter-global.com

www.stackdoor.eu



DISTRIBUTOR

V1_05-25