



STACKDOOR®

STACKDOOR RC3 DATASHEET



ACCREDITATIONS

- Independently tested to EN1627:2021 burglar resistant security standard.
- Certified to EN1627 RC3 level.

TYPICAL APPLICATIONS

- High risk retail buildings
- Airports and transport hubs
- Vandal resistant applications
- Multi-use car parks

STACK TECHNOLOGY

- More than 80% free airflow
- Small stacking zone at high level
- Self-locking to prevent lifting with no auxiliary locks
- Stainless steel curtain construction

OPTIONS

- Optional brushed stainless steel or powder coat finish to horizontal bars
- High or low duty cycle electrical motors
- Integration with third party controls



STACKDOOR®

STACKDOOR RC3 DATASHEET

STACKDOOR CURTAIN

- Steel pins secured into horizontal stainless steel profiles

BOTTOM RAIL AND FRAMES

- Reinforced stainless steel bottom rail section
- Heavy duty extruded aluminium guide rails anchored direct to the structure

OPERATION

- Motorised to allow controlled ascent and descent
- Tube Motor - Low duty cycle, for application up to 4 cycles per day
- External Drive Motor - High duty cycle for heavy use applications and/or larger apertures

CONTROLS

- Range of compatible controls including rotary switch, key switch, remote (control) and emergency manual crank
- Integration with 3rd Party access control system
- Safety supplied as design risk assessment directs

APPROVED DIMENSIONS

- Minimum width: 760mm
- Maximum width: 6000mm
- Minimum height: 2000mm
- Maximum height: 6000mm



SUBSTRATES

- **Certified installation onto:**
- Blockwork
- Concrete
- Structural Steelwork
- Sub assembly steel framework

**CHARTER
GLOBAL**

PROTECTING PEOPLE | SECURING PROPERTY

🏠 1 Darwin Close, Reading RG2 0TB United Kingdom

☎ +44 (0)845 050 8705 ✉ stackdoor@charter-global.com

www.stackdoor.eu

DISTRIBUTOR

V1_02-26